

GOLDRING



EST. 1906

Goldring Eroica LX Cartridge



The Eroica LX is a true audiophile moving-coil cartridge featuring the famous Gyger II diamond stylus profile. A nude, fine-line elliptical type with a 6 μm lesser radius, it gives smooth, extended highs, low distortion and reproduces a highly detailed and dynamic sound. To take proper advantage of this, the pick-up coils are hand-wound on a pure iron armature and suspended in a magnetic circuit of advanced design featuring low mass and powerful rare earth magnets. The low output Eroica LX offers an exceptionally high standard of performance and reliability and must be used with an amplifier which features a dedicated moving coil phono input.

GOLDRING



EST. 1906

Features

Frequency Response: 20 Hz - 22 kHz \pm 2 dB

Channel Balance: within 1 dB @ 1 kHz

Channel Separation: better than 25 dB @ 1 kHz

Sensitivity: 0.5 mV \pm 1dB, 1kHz @ 5 cm/sec

Static Compliance: 18 mm/N

Equivalent tip mass: 0.35 mg

Vertical Tracking Angle: 24 °

Stylus Radius: Gyger II

Stylus Type: Non-Replaceable

Load Resistance: 100 Ω

Load Capacitance: 100 - 1000 pF

Internal Inductance: 12 μ H

Internal Resistance: 8 Ω

Cartridge Mass: 5.5 g

Cartridge Mass (inc. fixings): 6.6 g

Fixing Centre: 0.5 " (12.7 mm)

Playing Weight: 1.5 - 2.0 g (1.7 g nom.)

GOLDRING



EST. 1906

Goldring Eroica LX Stylus

A Gyger II diamond stylus profile, a nude, fine-line elliptical type with a 6 μm lesser radius, which gives smooth, extended highs, low distortion and reproduces a highly detailed and dynamic sound.

Features

Stylus Radius: Gyger II

Stylus Type: Non-Replaceable